



P2V 15 - Modèle B

Fulfil all ergonomic demands

- 38.1 cm (15")-LCD panel (active matrix)
- Integrated touch screen
- Maximum resolution: 1024x768 pixels
- Video modes: VGA, SVGA, XGA
- Reaction time: 15/20 ms

Specifications

Display Features	
Screen Diagonal	30,8 cm (12,1") TFT LCD
Power Input	AC 90~264 V, 50~60 Hz.
Display Area	264x185 mm (HxV)
Contrast Ratio	300:1
Pixel Pitch	0.3075x0.3075 mm (HxV)
View Angle	R/L +45°~-45° U/D +30°~-10°
Resolution	SVGA 1024x768 75 Hz (max.)
Brightness	160 cd/m2
Response Time	30 ms
Connectors	Analog RGB, R/L Audio, 15-pin-D-SUB
User's Control	
Front Panel Controls	Auto Adjust, Menu, up, down, Power
Physical Specification	
Dimensions	304x244x143 mm (HxWxD)
Net Weight	2.6 kg
Power	
Power Saving	VESA DPMS Standard
Power Consumption	20W (Typ.)
Resistive Touch Panel	
Input Mode	Stylus Pen or Finger
Operation Temp.	-10°C~70°C
Hardness	3H
Transparency	>80%
Controller Type	USB

Your Dealer