



# 15D1 15" All-in-One Touchcomputer

Versatile All-in-One Touchcomputer Brings Style, Flexibility and Functionality to POS, Retail and Hospitality Environments

**Elo TouchSystems 15D1 15" All-in-One Touchcomputer expands the high profile Elo family** of reliable, easy-to-integrate multi-function touch solutions. The 15D1 brings style, flexibility and functionality to point-of-sale (POS), retail and hospitality businesses. With a wide array of field-installable peripherals, spill-resistant sealing, and a wide range of input/output port connection options, the 15D1 is versatile and powerful. It is designed with the future in mind, allowing easy serviceability of the main components and excellent performance utilizing the Intel Celeron 1.8 GHz processor.

The 15D1 features a sealed touchscreen resisting intrusion of dust and dirt, two-watt/channel speakers in the base and an accessible hard drive. It also supports Microsoft Windows XP, WEPOS, and Vista and is available with a variety of industry-leading Elo touch technologies including the innovative, aesthetic look of the zero-bezel Acoustic Pulse Recognition (APR), IntelliTouch surface acoustic wave and AccuTouch 5-wire resistive. POS peripherals that are easily installed in the field include: magnetic strip reader (MSR) for reading credit cards, ID cards, loyalty cards, etc., a rear-facing display for viewing customer transactions, a biometric fingerprint reader for added security, and a single 1-D or omni-directional 2-D barcode scanner.

## Features

- Field-installable peripherals
- Field-replaceable motherboard, hard drive, and power supply
- Excellent cable management; cables hidden from view
- 3 serial (2 powered serial), 7 USB 2.0, Ethernet 100/10 Base-T, Cash drawer, 2 PS/2, Audio (1 line-in, 1 line-out, 1 mic-in)
- 3-year warranty

## Benefits

- Minimizes downtime with peripherals that are easily installed in the field rather than factory
- Easy serviceability minimizes downtime
- Eliminate accidental disconnection and give a clean, professional look
- Accessible POS-focused input/output ports make installation of peripherals easy
- Customer satisfaction and peace of mind



# 15D1 15" All-in-One Touchcomputer

## Computer Specifications

Case/bezel color	Dark gray
Display	Size: 15.0" diagonal; Type: Active matrix TFT LCD; Aspect ratio: 4 x 3
Computer dimensions (max.)	Width: 13.58" (345 mm); Height: 11.34" (288 mm); Depth: 8.35" (212 mm) Dimensions vary with tilt angle and options selected
Processor	Intel Celeron-430 1.8GHz 512K L2 Cache 800MHz FSB LGA775 Pkg
Memory (RAM)	512MB 667MHz DDR2 standard on one slot; Expandable up to 4GB max [DDR2-667 (PC2-5400) or DDR2-800(PC2-6400)]; Dual Channel
Optional operating systems	Microsoft Windows XP Professional Service Pack 3; Microsoft Windows Embedded for Point of Sale (WEPOS); Microsoft Windows Vista Business
Languages	English, French, Italian, German, Spanish, Japanese, Simplified Chinese, Traditional Chinese
Serial ports	3 x serial ports; 2 x powered serial ports (5V default/12V; selectable via jumper)
USB ports	7 x USB2.0 ports
Parallel port	1 x Parallel port
Ethernet 100/10Base-T port	1 x LAN RJ45
Cash drawer port	1 x cash drawer (12V/24V default; selectable via jumper); Compatible with the following APG models: MultiPRO 320 with CD-005A cable; MultiPRO 420 with CD-039A cable
PS/2 port	2 x PS/2 (Keyboard and Mouse)
Audio port	1 x 3.5mm line-in; 1 x 3.5mm line-out; 1 x 3.5mm mic-in
Hard disk drive	1 x 2.5" SATA hard drive, 80GB minimum; Optional 2nd 80GB hard drive available
Compact flash slot	1 x compact flash type I
Wireless	Wireless kit available (802.11g 54Mbps)
Power supply	Internal PSU (270 W)
Power rating	Touchcomputer (without peripherals, receipt printer, cash drawer or power serial ports connected): 169.95 W max.; Cash Drawer: 2.4 W max.; Receipt printer: 45.6 W max.; Powered serial ports: 24 W max.; Total power drawn with all possible peripherals: 252.45 W max.
Options	Magnetic stripe reader; Customer display (20x2 VFD); Biometric fingerprint reader; Single line barcode scanner; Omni-directional barcode scanner; Second 80GB hard drive; Wireless card; Printer power cable
Temperature	Operating: 0°C to 35°C; Storage: -20°C to 60°C
Humidity	Operating: 20%-80%; Storage: 5%-95%; noncondensing
Weight (approx.)	With all options. Actual: 22.1 lb (10.03 kg); Shipping: 26.8 lb (12.16 kg)
Warranty	3 years
Agency approvals	UL/cUL, CE, BSMI, NOM, AR, CCC, EK, KCC, GOST-R, RCM, C-Tick, VCCI
User's controls	Brightness, contrast, phase, auto adjust, H-position, V-position, clock, sharpness, RGB, OSD H-position, OSD V-position, OSD time, OSD language (English, French, Italian, German, Spanish, Japanese, Simplified and Traditional Chinese), recall, power button (All control buttons lockable)

## Display Specifications

Useful screen area	Horizontal: 11.98" (304.128 mm); Vertical: 8.98" (228.096 mm)
Optimal (native) resolution	1024 x 768
Colors	16.2 million colors
Brightness	LCD panel: 250 cd/m <sup>2</sup> typical; with AccuTouch: 200 cd/m <sup>2</sup> typical; with Acoustic Pulse Recognition: 225 cd/m <sup>2</sup> typical; with IntelliTouch: 225 cd/m <sup>2</sup> typical
Response time	8.3 msec (typical)
Viewing angle (from center)	Horizontal (left/right): ±70° or 140° total; Vertical (up/down): 60°/65° or 125° total
Contrast ratio	700:1
Backlight lamp life	Minimum 50,000 hours to half brightness
MTBF	50,000 hours demonstrated

To find out more about Elo's extensive range of touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

### North America

800-ELO-TOUCH  
Elo TouchSystems  
Tel 1-650-361-4800  
301 Constitution Drive  
Fax 1-650-361-4722  
Menlo Park, CA 94025-1110  
[customerservice@elotouch.com](mailto:customerservice@elotouch.com)

### Europe

Tel +32 (0)16 35 21 00  
Fax +32 (0)16 35 21 01  
[elosales@elotouch.com](mailto:elosales@elotouch.com)

### Asia-Pacific

Tel +81 (45) 478-2161  
Fax +81 (45) 478-2180  
[www.tps.co.jp](http://www.tps.co.jp)

### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
[www.elotouch.com.ar](http://www.elotouch.com.ar)



Tyco Electronics reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

AccuTouch, Elo TouchSystems, IntelliTouch, TE Logo, and Tyco Electronics are trademarks.  
Copyright 2008 Tyco Electronics Corporation 12/08



Our commitment. Your advantage.