

# BIXOLON Samsung Label Printer Thermal Transfer **SLP-T400**

High Performance and Reliable, SLP-T400



The **BIXOLON Samsung SLP-T400** is the most comprehensive, cost-effective line of industrial thermal transfer label printing product in the marketplace today.

The **SLP-T400** is an ideal for a wide array of mission critical bar code labeling including 2D such as Maxicode, PDF417, QR Code and Data Matrix applications found in industries. In fact, where intricate two-dimensional bar coding is required for compliance labeling, small parts tracking, or product identification, the **SLP-T400** has emerged as the printer of choice by large, multinational operations.

This easy-to-use, low-maintenance printer SLP-T400 reduces training requirements and operating costs, and provides flexible solutions through a variety of options and accessories.

**The High Performance and Reliable, SLP-T400 integrates easily into a variety of mid-to low-volume printing applications including:**

- \* Warehousing - inventory control, asset management
- \* Transfer/Distribution - outer box, shipping, delivery, pallet
- \* Healthcare specimen labeling and patient tracking
- \* Retail product marking, shelf labeling, and coupon and receipt printing
- \* Transportation / Logistics
- \* Ticketing - events entry tickets
- \* General industry & manufacturing labeling requirements

## **BIXOLON Co., Ltd.**

980-3, Digital Empire Building A, Yeongtong-dong,  
Yeongtong-gu, Suwon, Gyeonggi-do, Korea, 443-813  
Tel : +82 31 218 5500 / Fax : +82 31 218 5589  
e-mail : sales@samsungminiprinter.com  
[www.samsungminiprinters.com](http://www.samsungminiprinters.com)

Distributored by:

**BIXOLON**® 

## Specifications for the SLP-T400

- \* **Thermal Transfer & Direct Thermal printing**
- \* **203 dpi (8dots/mm) / 300 dpi (12dots/mm, Optional)**
- \* **Fast Printing Speed up to 150mm/sec (6 ips)**
- \* **Wide range of paper width from 25mm to 112mm**
- \* **All in one interface support**  
Serial / Parallel / USB (All in one board) - Standard  
Ethernet (Internal / External) - Optional  
Bluetooth - Optional
- \* **Intensive Memory**  
Standard : 2 MB (16Mb) Flash  
512 (4Mb) SRAM
- \* **Various barcode types supported**  
1D : All types of one dimension supported  
2D : Maxicode, PDF417, QR Code, Data Matrix
- \* **Large Label & Ribbon Capacity**  
Paper Roll : OD - Max  $\Phi$  130mm(5.1")  
Ribbon Length : 74m, 100m, 300m  
Ribbon Size : Core ID 25mm(1") , OD 67mm(2.6")  
ID 13mm(0.5") , OD 33mm(1.3")
- \* **User-convenience**  
Movable Gap Sensor (Left <-> Right)  
User-defined software tool supported  
: Virtual Memory Switch Manager (VMMSM)  
20 kinds of code pages supported  
10 Size resident fonts supported  
PCX, BMP supported
- \* **Full range of options**  
Auto Cutter, External paper supplier  
**RFID supported**
- \* **Small footprint**  
Dimensions : 214(W) X 310(D) X 200(H) mm

