

Model C2202-PD




C2202-PD

Included items

- Display unit
- Base unit
- Short pole
- Long pole
- AC adapter
- AC cable
- Interface cable
(DB25 female – DB9 male)
- User's manual

Connector layout of base unit



Specifications

Display method	Vacuum fluorescent display
Display color	Blue green
Number of character	20 columns x 2 lines
Brightness	700cd/m ²
Character font	5 x 7 dot matrix, comma, decimal point
Character size (W x H)	5.25 x 9.2mm
Character pitch	8.3mm
Code page	PC-437/850/860/863/865, Slavonic, Russian, Katakana
Emulation	CBM standard, ESC/POS*
Interface	RS-232C (with path through function)
Power supply	12V DC
Power consumption	4.5W
MTBF	25,000 hours
Dimensions (W x H x D)	230 x 100 x 42mm
Viewing angle	±30 degrees
Rotation angle	Maximum 270 degrees
Weight	0.9kg
Safety standard	FCC class B, CE marking

*ESC/POS is a trademark of Seiko Epson Corporation

Japan CBM Corporation

Information Systems Division
 5-68-10 Nakano, Nakano-ku, Tokyo, 164-0001 Japan
 Tel: (81)-3-5345-7540
 Fax: (81)-3-5345-7541
<http://www.jcbm.co.jp/>
 e-mail: info-sys@jcbm.co.jp