



VFD-200

VFD-200 Series are VFD customer displays with elegant and ergonomic design, bright and easy to eyes display. The adjustable panel provides the best viewing angle max. 53 and horizontal rotation max. 360 .

FEATURES

- Display 2 x 20 characters
- Adjustable display angle and height
- Large and easy to read display
- Pass-through function to save cable connection
- Compatible with 9 different command sets or ESC/POS command
- RS-232 interface at 9600 baud rate
- USB interface without external power adaptor available for VFD-200
- Telescopic pole 270mm



SPECIFICATIONS

Customer Display		Tube Display
Display Pattern		Vacuum Fluorescent Display 5x7 dot matrix
Brightness	500 cd/m ²	
Character Type	96 alphanumeric & 13 international characters	
Command Set	9 different command sets	
Character Size	3.75Wx4.75H mm	
Character Number		2x20
		Electrical
Power Source	DC 9V~12V (RS-232) or DC 5V (USB)	
Power Consumption	2.5 Watts (RS-232) or 3 Watts (USB)	
Central Control Unit	CPU 8031BH ROM 64K flash ROM 32K SRAM	
Speed		29 Mhz
		Physical
Dimensions (Panel)	165Wx39Dx67H mm	
Dimensions (Support)	72mm	
Dimensions (Base)	187Wx84Dx25H mm	
Tilt Angle		Max. 53°
Rotation Angle		Max. 360°
Weight	0.56Kg	
Interface	RS-232/USB	
Color		Black or beige
		Environmental
Operating Temperature	0°C~40°C (32°F~104°F)	
Storage Temperature	-10°C~50°C (14°F~122°F)	
Relative Humidity	0%~90% RH	

