

# P2V L-3 – Midrange Label Printer

www.metapace.com

## Highlights

- Produces labels with direct thermal or thermal transfer printing
- Prints up to 116 mm wide labels at a max. speed of 254 mm/sec. at 8 dots/mm (203 dpi)
- Robust construction: intelligent features in a massive steel housing
- Free of charge: professional label printing software included in scope of delivery
- Large supply of labels - quick access for exchanging consumables

## Technical specifications

### Print

Printing method	Direct thermal, thermal transfer
Print width	Max. 104mm
Print length	Max. 4000mm
Print speed	Max. 254mm/s
Resolution	8dots/mm (203dpi)

### Label roll

Width	Max. 116mm
Thickness	0.06mm - 0.305mm
Size	Max. external diameter: 203mm; min. core diameter: 38mm

### Ink ribbon

Width	Max. 118mm
Length	Max. 600m
Size	Max. external diameter: 84mm; min. core diameter: 25.4mm
Winding	Internal or external

### Electronics

Emulation	EPL, ZPL
Sensors	Reflective/transmissive
Memory	4MB Flash ROM; 8MB SDRAM
Power supply	Input: AC 240V ± 10%, 50/60Hz (integrated)
Fonts	Five integrated ASCII fonts, optional multi-language fonts
Display	LCD, 2 line graphic

### Specifics

Options	Cutter, 12 dots/mm (300dpi); 24 dots/mm (600dpi) version
---------	--

### Interfaces

I/F ports	RS232, USB 1.1, PS2, Centronics, Ethernet (optional)
-----------	--

### Software

Drivers	Windows 2000, XP (32 Bit), Vista (32 Bit), Windows 7 (32 Bit)
Software	Incl. label printing software (full version)

### Operating temperature

Temperature	0°C - 40°C
Humidity	5% - 85% non-condensing

### Housing

Dimensions (WxHxD)	286x280x448mm
Weight	15kg
Colour	Black

### Warranty

Period	24 months
--------	-----------



**L-3**  
**METAPACE**