

P2V 15 MULTI

LCD Monitor with Multitouch Screen



- High-end 38.1 cm (15") LCD monitor for most demanding applications
- Integrated multitouch screen with bezel-free glass surface
- Highly elegant design featuring an extremely robust construction
- Works without driver software (as of Windows 7)
- Complete package including USB cable, audio cable and PSU

Specifications

Display	LCD size / type	38.1 cm (15") TFT active matrix panel
	Touch technology	Projective capacitive
	Touch interface	USB
	Visible surface	304x228 mm (HxV)
	Pixel pitch	0.297 x 0.297 mm (HxV)
	Resolution	1024 x 768 pixel
	Display mode	VGA 720x400 (70 Hz), VGA 640x480 (60/66/72/75 Hz), SVGA 800x600 (56/60/72/75 Hz), XGA 1024x768 (60/70/75 Hz)
	Display colours	16.2 millions
	Contrast	500:1
	Brightness (capacitive)	225 cd/m ² (typical)
	Response time	8 ms (typical)
	Viewing angle	Horizontal: 140° / vertical: 125°
General	Video input format	Analogue RGB 0.7V peak to peak
	Video input frequency	Horizontal: 31.47 kHz~60.02 kHz / vertical: 56 Hz~75 Hz
	Video signal input	15-pin D-sub (female, analogue)
	Colour	Black
	Dimensions	322x364x206 mm (HxWxD)
	Weight / Shipping weight	5.54 kg / 7.7 kg
	Voltage	AC input 100~240V / DC 12V
	Power consumption	Operation: 25W / standby: 3W / off: 1W
	Mounting options	Stand / 75x75 mm VESA wall mount
	Function keys	Power on/off, Select, Up, Down, Menu
	Audio	1W speakers, 2 channels
	Temperature - operation / storage	0°C~40°C / -20°C~60°C
Humidity - operation / storage	20%~80% / 10%~90% (non-condensing)	



Your Dealer