

15" Multi Touch Monitor

Features

- True Flat designed to suit harsh environment
- Projective Capacitive touch (M467PB) / Resistive Touch (M467TB/M467RB)
- Die-casting Aluminum Housing
- Smart Cable Management
- Detachable Stand / Support VESA mounting
- Spill proof & Anti-dust
- Support 2nd Display & MSR



M467



Adjustable viewing angle up to 90 degrees



Spill proof at front panel



Elegant design with projective capacitive touch



Unique base design with smart cable management



Support 2nd Display



MSR Attached

Specifications

Model	M467TB	M467PB
Display Size	15"	
Optimal Resolution	1024 * 768	
Panel Brightness	250 cd/m ² (typ)	
Contrast Ratio	600:1 (typ)	
Response Time	8 ms (typ)	
Viewing Angle	160°(H)/160°(V)	
Input Video signal	D-Sub 15 pins / DVI-D	
Touch Function	Resistive Touch(USB or RS232 Interface)	Projective Capacitive Touch(USB Interface)
Power consumption	20W operation / 3W standby	
Input Frequency	Horizontal: 31.5-60.2 kHz ; Vertical: 56.3Hz-75Hz	
Power supply	DC 12V +/- 10%	
Temperature	Operating : 0°C~40°C ; Storage : -10°C~50°C	
Humidity	Operating : 20%~80% ; Storage : 10%~90%	
Weight	4.67 kgs (net)	
Physical Dimension WxHxD(mm)	365.2 (W) * 338.6 (H) * 200 (D)	
Optional	M36X 2nd Display, Wall mount, White Color, MSR,Front Bezel Design	

Product specification subject to change without prior notice.

OTEK SYSTEM CO., LTD.

Address: 6F, 30 Sinjhong Rd., Neihu District, Taipei 114, Taiwan Tel: 886-2-7720-1688 Fax: 886-2-7721-2188

http://www.oteksys.com sales@oteksys.com

M467a-1110

