

12.1", 15", 17" Touch Monitor

Features

- Resistive touch monitor
- Spill proof & anti dust
- Smart cable management
- Wall-mount supporting
- Support 2nd display & MSR



OT12



OT15



OT17



Specifications

Model	OT12TA/ OT12TB	OT15TA OT15TB	OT17TA OT17TB
Display size	12.1"	15"	17"
Display Area	246 * 184 mm	304 * 228 mm	338 * 270 mm
Optimal Resolution	1024 X 768		1280 X 1024
Panel Brightness	500 cd/m ² (typ)		250 cd/m ² (typ)
Contrast Ratio	700 : 1		1000 : 1
Response Time	26 ms (typ)		5 ms (typ)
Viewing Angle	160 degrees (H) 140 degrees (V)		170 degrees (H) 160 degrees (V)
Input Video signal	D-Sub 15 pins D-Sub 15 pins+DVHD	D-Sub 15 pins D-Sub 15 pins+DVHD	D-Sub 15 pins D-Sub 15 pins+DVHD
Power consumption	10W		30W
Input Frequency	Horizontal : 31.5 kHz~60.2 kHz Vertical : 56.3Hz~75Hz		
Power supply	DC 12V +/- 10%		
Temperature	Operating : 0°C~40°C Storage : -10°C~50°C		
Humidity	Operating : 20%~80% Storage : 10%~90%		
Weight	4.5Kg(net)	4.67Kg(net)	5.86Kg(net)
Wall Mount	VESA 75 * 75 mm		VESA 100 * 100 mm
Optional	VFD 2X20, 2nd Display (OT07, OT84), MSR, Wall Mount Bracket		

This specification is subject to change without prior notice.

OTEK SYSTEM CO., LTD.

Address: 6F, 30 Sinjhong Rd., Neihu District, Taipei 114, Taiwan Tel: 886-2-7720-1688 Fax: 886-2-7721-2188
<http://www.oteksys.com> sales@oteksys.com

OT15a-1201

